# SAFETY DATA SHEET BRAKE CLEANER 300ML



# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name BRAKE CLEANER 300ML

Product No. BIRI04

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

# 1.3. Details of the supplier of the safety data sheet

Supplier James Briggs Limited

Salmon Fields, Royton,

Oldham, Lancashire

OL2 6HZ, England 0161 627 0101

sds@jamesbriggs.co.uk

# 1.4. Emergency telephone number

### **SECTION 2: HAZARDS IDENTIFICATION**

### 2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical and Chemical Hazards Flam. Aerosol 1 - H222

Human health Skin Irrit. 2 - H315;STOT SE 3 - H336

Environment Aquatic Chronic 2 - H411

# 2.2. Label elements

Label In Accordance With (EC) No. 1272/2008







Signal Word	Danger

Hazard Statements

H222 Extremely flammable aerosol.
H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.H411 Toxic to aquatic life with long lasting effects.

**Precautionary Statements** 

P102 Keep out of reach of children.

P271 Use only outdoors or in a well-ventilated area.

P261 Avoid breathing vapour/spray.
P280 Wear protective gloves.

P302+352 IF ON SKIN: Wash with plenty of soap and water.

P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P332+313 If skin irritation occurs: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local regulations.

Supplementary Precautionary Statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after use.

P264 Wash contaminated skin thoroughly after handling.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P362 Take off contaminated clothing and wash before reuse.

P410+412 Protect from sunlight. Do not expose to temperatures exceeding 50

°C/122°F.

Supplemental label information

Contains:

SOL021 Hydrocarbons, C6 - C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

H229 Pressurised container: May burst if heated

#### 2.3. Other hazards

None noted

#### **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.2. Mixtures

BUTANE 5-10%

CAS-No.: 106-97-8 EC No.: 203-448-7 Registration Number: Exempt - Naturally occuring

Classification (EC 1272/2008) Classification (67/548/EEC)

Flam. Gas 1 - H220 F+;R12

HYDROCARBONS, C6-C7, N-ALKANES, ISOALKANES, CYCLICS, <5% N-HEXANE 60-100%

CAS-No.: EC No.: 921-024-6 Registration Number: 01-2119475514-35-XXXX

Classification (EC 1272/2008) Classification (67/548/EEC)

 Flam. Liq. 2 - H225
 Xn;R65.

 Skin Irrit. 2 - H315
 Xi;R38.

 STOT SE 3 - H336
 F;R11.

 Asp. Tox. 1 - H304
 N;R51/53.

 Aquatic Chronic 2 - H411
 R67.

ISOBUTANE 1-5%

CAS-No.: 75-28-5 EC No.: 200-857-2 Registration Number: Exempt - Naturally occuring

Classification (EC 1272/2008) Classification (67/548/EEC)

Flam. Gas 1 - H220 F+;R12

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

#### **SECTION 4: FIRST AID MEASURES**

# 4.1. Description of first aid measures

General information

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

Inhalation

Move the exposed person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep the affected person warm and at rest. Get prompt medical attention.

Ingestion

DO NOT INDUCE VOMITING! Rinse mouth thoroughly with water and give large amounts of milk or water to people not unconscious. Get medical attention if any discomfort continues.

Skin contact

Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

Eye contact

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

# 4.2. Most important symptoms and effects, both acute and delayed

General information

Not applicable

### 4.3. Indication of any immediate medical attention and special treatment needed

Not applicable

#### **SECTION 5: FIREFIGHTING MEASURES**

#### 5.1. Extinguishing media

Extinguishing media

Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

# 5.2. Special hazards arising from the substance or mixture

Unusual Fire & Explosion Hazards

Aerosol cans may explode in a fire.

### 5.3. Advice for firefighters

Special Fire Fighting Procedures

Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.

### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Not applicable

# 6.2. Environmental precautions

Not applicable

# 6.3. Methods and material for containment and cleaning up

Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Let evaporate. Keep out of confined spaces because of explosion risk. If leakage cannot be stopped, evacuate area.

# 6.4. Reference to other sections

Not applicable

### **SECTION 7: HANDLING AND STORAGE**

#### 7.1. Precautions for safe handling

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

# 7.2. Conditions for safe storage, including any incompatibilities

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

# 7.3. Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1. Control parameters

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
BUTANE	WEL	600 ppm	1450 mg/m3	750 ppm	1810 mg/m3	
HYDROCARBONS, C6-C7, N-ALKANES, ISOALKANES, CYCLICS, <5% N-HEXANE			1200 mg/m3	60 ppm	216 mg/m3	

WEL = Workplace Exposure Limit.

### 8.2. Exposure controls

Protective equipment





Engineering measures

Provide adequate general and local exhaust ventilation.

Respiratory equipment

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit. Use chemical cartridge protection with appropriate cartridge.

Hand protection

Use protective gloves.

Eye protection

Use approved safety goggles or face shield.

Other Protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

### **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

# 9.1. Information on basic physical and chemical properties

Appearance Aerosol.

Colour Typical

Odour Characteristic.

Flammability Limit - Lower(%) 0.8 Flammability Limit - Upper(%) 9.0

# 9.2. Other information

Not determined.

### **SECTION 10: STABILITY AND REACTIVITY**

# 10.1. Reactivity

Not determined

# 10.2. Chemical stability

Stable under normal temperature conditions.

# 10.3. Possibility of hazardous reactions

Not determined.

### 10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising agents. Strong alkalis. Strong mineral acids.

# 10.5. Incompatible materials

Materials To Avoid See section 10.4

# 10.6. Hazardous decomposition products

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

# **SECTION 11: TOXICOLOGICAL INFORMATION**

### 11.1. Information on toxicological effects

#### Inhalation

May cause irritation to the respiratory system. Vapours may cause headache, fatigue, dizziness and nausea. Prolonged inhalation of high concentrations may damage respiratory system. Irritating to respiratory system.

#### Ingestion

May cause discomfort if swallowed. May cause stomach pain or vomiting. Gastrointestinal symptoms, including upset stomach.

#### Skin contact

Prolonged or repeated exposure may cause severe irritation. Acts as a defatting agent on skin. May cause cracking of skin, and eczema. May cause allergic contact eczema. May cause sensitisation by skin contact. Irritating to skin.

#### Eye contact

Irritating to eyes. May cause chemical eye burns.

Route of entry

Inhalation. Skin and/or eye contact.

### **SECTION 12: ECOLOGICAL INFORMATION**

**Ecotoxicity** 

Dangerous for the environment if discharged into watercourses.

# 12.1. Toxicity

Not applicable

#### 12.2. Persistence and degradability

Not applicable

#### 12.3. Bioaccumulative potential

Bioaccumulative potential

No data available on bioaccumulation.

# 12.4. Mobility in soil

Mobility:

Not determined

# 12.5. Results of PBT and vPvB assessment

Not applicable

### 12.6. Other adverse effects

Not determined.

### **SECTION 13: DISPOSAL CONSIDERATIONS**

General information

Dispose of in accordance with Local Authority guidelines.

### 13.1. Waste treatment methods

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.

### **SECTION 14: TRANSPORT INFORMATION**

# 14.1. UN number

UN No. (ADR/RID/ADN) 1950 UN No. (IMDG) 1950 UN No. (ICAO) 1950

# 14.2. UN proper shipping name

Proper Shipping Name AEROSOLS

# 14.3. Transport hazard class(es)

ADR/RID/ADN Class 2

ADR/RID/ADN Class Class 2: Gases

ADR Label No. 2.1

IMDG Class 2.1

ICAO Class/Division 2.1

Transport Labels



### 14.4. Packing group

ADR/RID/ADN Packing group Not Applicable
IMDG Packing group Not Applicable
ICAO Packing group Not Applicable

### 14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant No.

### 14.6. Special precautions for user

EMS F-D, S-U

# 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

### **SECTION 15: REGULATORY INFORMATION**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Statutory Instruments

The Aerosol Dispensers (Amendment) Regulations 2014 No.1130

**Guidance Notes** 

Workplace Exposure Limits EH40.

Introduction to Local Exhaust Ventilation HS(G)37.

**EU** Legislation

The Aerosol Dispensers Directive 1975/324 EEC

Regulation (EC) No.1272/2008 The Classification, Labelling and Packaging of substances and mixtures Regulations

Regulation (EC) No. 1907/2006 The Registration, Evaluation, Authorisation and Restriction of Chemicals Regulations (REACH)

2001/95/EC The General Product Safety Directive (GPSD)

Commission Regulation (EU) 2015/830 Requirements for the compilation of safety data sheets (amending REACH)

Authorisations (Title VII Regulation 1907/2006)

No specific authorisations are noted for this product.

Restrictions (Title VIII Regulation 1907/2006)

No specific restrictions of use are noted for this product.

# 15.2. Chemical Safety Assessment

## **SECTION 16: OTHER INFORMATION**

Revision Date 26/08/2016

Revision

Supersedes date

Hazard Statements In Full

H220 Extremely flammable gas. , H222 Extremely flammable aerosol. , H225 Highly flammable liquid and vapour. , H304 May be fatal if swallowed and enters airways. , H315 Causes skin irritation. , H336 May cause drowsiness or dizziness. , H411 Toxic to aquatic life with long lasting effects.

21/11/2013