# SAFETY DATA SHEET H17 NILCO LEATHER CLEANER & RENOVATOR (SRP) 500ML

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product identifier

Product name	H17 NILCO LEATHER CLEANER & RENOVATOR (SRP) 500ML
Product No.	SVTN500LCRSR

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses As product description

## 1.3. Details of the supplier of the safety data sheet

Supplier

James Briggs Limited Salmon Fields, Royton, Oldham, Lancashire OL2 6HZ, England 0161 627 0101 sds@jamesbriggs.co.uk

## 1.4. Emergency telephone number

National Emergency Telephone Number Hazchem line: 0044 (0) 7970 779978

## SECTION 2: HAZARDS IDENTIFICATION

## 2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical and Chemical HazardsFlam. Aerosol 1 - H222Human healthSTOT SE 3 - H336EnvironmentNot classified.

### 2.2. Label elements

Label In Accordance With (EC) No. 1272/2008



Signal Word	Danger	
Hazard Statements		
	H222	Extremely flammable aerosol.
	H336	May cause drowsiness or dizziness.
Precautionary Statements		
	P102	Keep out of reach of children.
	P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
	P211	Do not spray on an open flame or other ignition source.
	P251	Pressurized container: Do not pierce or burn, even after use.
	P271	Use only outdoors or in a well-ventilated area.
	P261	Avoid breathing vapour/spray.
	P501	Dispose of contents/container in accordance with local regulations.
Supplementary Precautionary Sta	atements	
	P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P312 P410+412 Call a POISON CENTER or doctor/physician if you feel unwell. Protect from sunlight. Do not expose to temperatures exceeding 50  $^\circ\text{C}/122^\circ\text{F}.$ 

Supplemental label information

H229

Pressurised container: May burst if heated

## 2.3. Other hazards

None noted

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

## 3.2. Mixtures

BUTANE		5-10%
CAS-No.: 106-97-8	EC No.: 203-448-7	Registration Number: Exempt - Naturally occuring
Classification (EC 1272/2008) Flam. Gas 1 - H220		Classification (67/548/EEC) F+;R12
ISOBUTANE		1-5%
CAS-No.: 75-28-5	EC No.: 200-857-2	Registration Number: Exempt - Naturally occuring
Classification (EC 1272/2008) Flam. Gas 1 - H220		Classification (67/548/EEC) F+;R12
NAPHTHA (PETROLEUM), HYDRO	TREATED HEAVY	10-30%
CAS-No.: 64742-48-9	EC No.: 919-857-5	Registration Number: 01-2119463258-33-XXXX
Classification (EC 1272/2008) Flam. Liq. 3 - H226 EUH066 STOT SE 3 - H336 Asp. Tox. 1 - H304		Classification (67/548/EEC) Xn;R65. R10,R66,R67.
SODIUM NITRITE		< 1%
CAS-No.: 7632-00-0	EC No.: 231-555-9	Registration Number: 01-2119471836-27-XXXX
Classification (EC 1272/2008) Ox. Sol. 3 - H272 Acute Tox. 3 - H301 Aquatic Acute 1 - H400		Classification (67/548/EEC) O;R8 T;R25 N;R50

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

## SECTION 4: FIRST AID MEASURES

#### 4.1. Description of first aid measures

General information

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

Inhalation

Move the exposed person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep the affected person warm and at rest. Get prompt medical attention.

#### Ingestion

DO NOT INDUCE VOMITING! Rinse mouth thoroughly with water and give large amounts of milk or water to people not unconscious. Get medical attention if any discomfort continues.

Skin contact

Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

Eye contact

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

## 4.2. Most important symptoms and effects, both acute and delayed

General information

NOTE! Effects may be delayed. Keep affected person under observation.

### 4.3. Indication of any immediate medical attention and special treatment needed

No specific first aid measures noted.

## SECTION 5: FIREFIGHTING MEASURES

## 5.1. Extinguishing media

Extinguishing media Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

## 5.2. Special hazards arising from the substance or mixture

Unusual Fire & Explosion Hazards Aerosol cans may explode in a fire.

## 5.3. Advice for firefighters

Special Fire Fighting Procedures

Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1. Personal precautions, protective equipment and emergency procedures

Not applicable

### 6.2. Environmental precautions

Not applicable

#### 6.3. Methods and material for containment and cleaning up

Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Let evaporate. Keep out of confined spaces because of explosion risk. If leakage cannot be stopped, evacuate area.

## 6.4. Reference to other sections

Not applicable

## SECTION 7: HANDLING AND STORAGE

#### 7.1. Precautions for safe handling

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

#### 7.2. Conditions for safe storage, including any incompatibilities

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

## 7.3. Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

Name	STD	TWA	- 8 Hrs	STEL	- 15 Min	Notes
BUTANE	WEL	600 ppm	1450 mg/m3	750 ppm	1810 mg/m3	
NAPHTHA (PETROLEUM), HYDROTREATED HEAVY			1000 mg/m3			

WEL = Workplace Exposure Limit.

## 8.2. Exposure controls

Protective equipment



Engineering measures

Provide adequate general and local exhaust ventilation.

Respiratory equipment

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit. Use chemical cartridge protection with appropriate cartridge.

Hand protection

Use protective gloves.

Eye protection

Wear approved chemical safety goggles where eye exposure is reasonably probable.

Other Protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

## 9.1. Information on basic physical and chemical properties

Appearance	Aerosol.
Colour	Typical
Odour	Characteristic.
Flammability Limit - Lower(%)	0.8
Flammability Limit - Upper(%)	9.0

## 9.2. Other information

Not determined.

SECTION 10: STABILITY AND REACTIVITY

#### 10.1. Reactivity

No specific reactivity hazards associated with this product.

### 10.2. Chemical stability

Stable under normal temperature conditions.

#### 10.3. Possibility of hazardous reactions

Not known.

## 10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising agents. Strong alkalis. Strong mineral acids.

### 10.5. Incompatible materials

Materials To Avoid See section 10.4

## 10.6. Hazardous decomposition products

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

## SECTION 11: TOXICOLOGICAL INFORMATION

## 11.1. Information on toxicological effects

Inhalation

May cause irritation to the respiratory system. Vapours may cause headache, fatigue, dizziness and nausea. Prolonged inhalation of high concentrations may damage respiratory system.

#### Ingestion

May cause discomfort if swallowed. May cause stomach pain or vomiting. Gastrointestinal symptoms, including upset stomach.

Skin contact

Prolonged or repeated exposure may cause severe irritation. Acts as a defatting agent on skin. May cause cracking of skin, and eczema.

Eye contact Irritating to eyes. May cause chemical eye burns. Route of entry Inhalation. Skin and/or eye contact.

## SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

Dangerous for the environment if discharged into watercourses.

## 12.1. Toxicity

Data set not currently available.

#### 12.2. Persistence and degradability

Not applicable

#### 12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

#### 12.4. Mobility in soil

Mobility: Not determined

#### 12.5. Results of PBT and vPvB assessment

Not applicable

#### 12.6. Other adverse effects

Not known.

#### SECTION 13: DISPOSAL CONSIDERATIONS

#### 13.1. Waste treatment methods

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.

SECTION 14: TRANSPORT INFORMATION

## 14.1. UN number

UN No. (ADR/RID/ADN)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950

## 14.2. UN proper shipping name

Proper Shipping Name	AEROSOLS
r toper Shipping Name	ALIGOUL

14.3. Transport hazard class(es)	
ADR/RID/ADN Class	2
ADR/RID/ADN Class	Class 2: Gases
ADR Label No.	2.1
IMDG Class	2.1
ICAO Class/Division	2.1
Transport Labels	



## 14.4. Packing group

ADR/RID/ADN Packing group	Not Applicable
IMDG Packing group	Not Applicable
ICAO Packing group	Not Applicable

## 14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant No.

## 14.6. Special precautions for user

EMS

F-D, S-U

## 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

# SECTION 15: REGULATORY INFORMATION

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Statutory Instruments The Aerosol Dispensers (Amendment) Regulations 2014 No.1130 Guidance Notes Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. EU Legislation The Aerosol Dispensers Directive 1975/324 EEC Regulation (EC) No.1272/2008 The Classification, Labelling and Packaging of substances and mixtures Regulations Regulation (EC) No.1907/2006 The Registration, Evaluation, Authorisation and Restriction of Chemicals Regulations (REACH) 2001/95/EC The General Product Safety Directive (GPSD) Commission Regulation (EU) 2015/830 Requirements for the compilation of safety data sheets (amending REACH) Authorisations (Title VII Regulation 1907/2006) No specific authorisations are noted for this product. Restrictions (Title VIII Regulation 1907/2006) No specific restrictions of use are noted for this product.

## 15.2. Chemical Safety Assessment

**SECTION 16: OTHER INFORMATION** 

Revision Date	06/06/2018
Revision	3
Supersedes date	10/11/2015
Hazard Statements In Full	

EUH066 Repeated exposure may cause skin dryness or cracking. , H220 Extremely flammable gas. , H222 Extremely flammable aerosol. , H226 Flammable liquid and vapour. , H272 May intensify fire; oxidiser. , H301 Toxic if swallowed. , H304 May be fatal if swallowed and enters airways. , H336 May cause drowsiness or dizziness. , H400 Very toxic to aquatic life.