

SAFETY DATA SHEET COOL ICE AIR FRESHENER 150ML

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

| Product name | AIR FRESHENER 150ML |
|--------------|---------------------|
| Product No. | DH429 |

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

James Briggs Limited Salmon Fields, Royton, Oldham, Lancashire OL2 6HZ, England 0161 627 0101 sds@jamesbriggs.co.uk

1.4. Emergency telephone number

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

| Physical and Chemical Hazards | Flam. Aerosol 1 - H222 |
|-------------------------------|------------------------|
| Human health | STOT SE 3 - H336 |
| Environment | Not classified. |

2.2. Label elements

Label In Accordance With (EC) No. 1272/2008



| Signal Word | Danger | |
|------------------------------------|----------|---|
| Hazard Statements | | |
| | H222 | Extremely flammable aerosol. |
| | H336 | May cause drowsiness or dizziness. |
| Precautionary Statements | | |
| | P102 | Keep out of reach of children. |
| | P501 | Dispose of contents/container in accordance with local regulations. |
| Supplementary Precautionary Stater | ments | |
| | P210 | Keep away from heat/sparks/open flames/hot surfaces No smoking. |
| | P211 | Do not spray on an open flame or other ignition source. |
| | P251 | Pressurized container: Do not pierce or burn, even after use. |
| | P410+412 | Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F. |
| Supplemental label information | | |
| | H229 | Pressurised container: May burst if heated |
| | | Contains: |
| | SOL012 | Propan-2-ol |
| 2.2 Other hererde | | |

2.3. Other hazards

None noted

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

| BUTANE | | 30-60% |
|---|-------------------|---|
| CAS-No.: 106-97-8 | EC No.: 203-448-7 | Registration Number: Exempt - Naturally occuring |
| Classification (EC 1272/2008) Flam. Gas 1 - H220 | | Classification (67/548/EEC) F+;R12 |
| ISOBUTANE | | 10-30% |
| CAS-No.: 75-28-5 | EC No.: 200-857-2 | Registration Number: Exempt - Naturally occuring |
| Classification (EC 1272/2008) Flam. Gas 1 - H220 | | Classification (67/548/EEC) F+;R12 |
| PROPAN-2-OL | | 10-30% |
| CAS-No.: 67-63-0 | EC No.: 200-661-7 | Registration Number: 01-2119457558-25-XXXX |
| Classification (EC 1272/2008) Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336 | | Classification (67/548/EEC) F;R11 Xi;R36 R67 |

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General information

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

Inhalation

Move the exposed person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep the affected person warm and at rest. Get prompt medical attention. Ingestion

DO NOT INDUCE VOMITING! Rinse mouth thoroughly with water and give large amounts of milk or water to people not unconscious. Get medical attention if any discomfort continues.

Skin contact

Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

Eye contact

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

General information

NOTE! Effects may be delayed. Keep affected person under observation.

4.3. Indication of any immediate medical attention and special treatment needed

No specific first aid measures noted.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

AIR FRESHENER 150ML

Extinguishing media Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

5.2. Special hazards arising from the substance or mixture

Unusual Fire & Explosion Hazards

Aerosol cans may explode in a fire.

5.3. Advice for firefighters

Special Fire Fighting Procedures

Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Not applicable

6.2. Environmental precautions

Not applicable

6.3. Methods and material for containment and cleaning up

Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Let evaporate. Keep out of confined spaces because of explosion risk. If leakage cannot be stopped, evacuate area.

6.4. Reference to other sections

Not applicable

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

7.2. Conditions for safe storage, including any incompatibilities

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

7.3. Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

| Name | STD | TWA | - 8 Hrs | STEL | - 15 Min | Notes |
|-------------|-----|---------|------------|---------|------------|-------|
| BUTANE | WEL | 600 ppm | 1450 mg/m3 | 750 ppm | 1810 mg/m3 | |
| PROPAN-2-OL | WEL | 400 ppm | 999 mg/m3 | 500 ppm | 1250 mg/m3 | |

WEL = Workplace Exposure Limit.

8.2. Exposure controls

Protective equipment



Engineering measures

Provide adequate general and local exhaust ventilation.

Respiratory equipment

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit. Use chemical cartridge protection with appropriate cartridge.

AIR FRESHENER 150ML

Hand protection

Use protective gloves.

Eye protection

Wear approved chemical safety goggles where eye exposure is reasonably probable.

Other Protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

| Appearance | Aerosol. |
|-------------------------------|-----------------|
| Colour | Typical |
| Odour | Characteristic. |
| Flammability Limit - Lower(%) | 0.8 |
| Flammability Limit - Upper(%) | 9.0 |

9.2. Other information

Not determined.

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No specific reactivity hazards associated with this product.

10.2. Chemical stability

Stable under normal temperature conditions.

10.3. Possibility of hazardous reactions

Not known.

10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising agents. Strong alkalis. Strong mineral acids.

10.5. Incompatible materials

Materials To Avoid See section 10.4

10.6. Hazardous decomposition products

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Inhalation

May cause irritation to the respiratory system. Vapours may cause headache, fatigue, dizziness and nausea. Prolonged inhalation of high concentrations may damage respiratory system.

Ingestion

May cause discomfort if swallowed. May cause stomach pain or vomiting. Gastrointestinal symptoms, including upset stomach.

Skin contact

Prolonged or repeated exposure may cause severe irritation. Acts as a defatting agent on skin. May cause cracking of skin, and eczema.

Eye contact

Irritating to eyes. May cause chemical eye burns.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

Dangerous for the environment if discharged into watercourses.

12.1. Toxicity

Data set not currently available.

12.2. Persistence and degradability

Not applicable

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

12.4. Mobility in soil

Mobility: Not determined

12.5. Results of PBT and vPvB assessment

Not applicable

12.6. Other adverse effects

Not known.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.

SECTION 14: TRANSPORT INFORMATION

14.1. UN number

| UN No. (ADR/RID/ADN) | 1950 |
|----------------------|------|
| UN No. (IMDG) | 1950 |
| UN No. (ICAO) | 1950 |

14.2. UN proper shipping name

| Proper Shipping Name | AEROSOLS |
|----------------------|----------|
|----------------------|----------|

14.3. Transport hazard class(es)

| ADR/RID/ADN Class | 2 |
|---------------------|----------------|
| ADR/RID/ADN Class | Class 2: Gases |
| ADR Label No. | 2.1 |
| IMDG Class | 2.1 |
| ICAO Class/Division | 2.1 |
| Transport Labels | |



AIR FRESHENER 150ML

14.4. Packing group

| ADR/RID/ADN Packing group | Not Applicable |
|---------------------------|----------------|
| IMDG Packing group | Not Applicable |
| ICAO Packing group | Not Applicable |

14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant No.

14.6. Special precautions for user

EMS

F-D, S-U

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Statutory Instruments The Aerosol Dispensers (Amendment) Regulations 2014 No.1130 Guidance Notes Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. EU Legislation The Aerosol Dispensers Directive 1975/324 EEC Regulation (EC) No.1272/2008 The Classification, Labelling and Packaging of substances and mixtures Regulations Regulation (EC) No. 1907/2006 The Registration, Evaluation, Authorisation and Restriction of Chemicals Regulations (REACH) 2001/95/EC The General Product Safety Directive (GPSD) Commission Regulation (EU) 2015/830 Requirements for the compilation of safety data sheets (amending REACH) Authorisations (Title VII Regulation 1907/2006) No specific authorisations are noted for this product. Restrictions (Title VII Regulation 1907/2006) No specific restrictions of use are noted for this product.

15.2. Chemical Safety Assessment

SECTION 16: OTHER INFORMATION

| Revision Date | 18/06/2018 |
|---------------------------|------------|
| Revision | 3 |
| Supersedes date | 07/02/2018 |
| Hazard Statements In Full | |

H220 Extremely flammable gas., H222 Extremely flammable aerosol., H225 Highly flammable liquid and vapour., H319 Causes serious eye irritation., H336 May cause drowsiness or dizziness.