



SAFETY DATA SHEET CARLUBE DOT 4 ESP BRAKE FLUID

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME	CARLUBE DOT 4 ESP BRAKE FLUID		
PRODUCT NO.	BFE050		
INTERNAL ID	S-Eth		
APPLICATION	Brake fluid.		
SUPPLIER	TETROSYL LIMITED BEVIS GREEN WORKS WALMERSLEY BURY BL9 6RE 0161 764 5981 0161 797 5899 info@tetrosyl.com	MANUFACTURER	TETROSYL LIMITED BEVIS GREEN WORKS WALMERSLEY BURY BL9 6RE 0161 764 5981 0161 797 5899 info@tetrosyl.com
EMERGENCY TELEPHONE	0161 764 5981		

2 HAZARDS IDENTIFICATION

CLASSIFICATION (1999/45) Xi;R36.

CLASSIFICATION (EC 1272/2008)

Physical and Chemical Hazards	Not classified.
Human health	Eye Irrit. 2 - H319;Repr. 2 - H361d
Environment	Not classified.

LABEL IN ACCORDANCE WITH (EC) NO. 1272/2008



SIGNAL WORD Warning
CONTAINS 2-(2-METHOXYETHOXY)ETHANOL
HAZARD STATEMENTS

H319	Causes serious eye irritation.
H361d	Suspected of damaging the unborn child.
PRECAUTIONARY STATEMENTS	
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P201	Obtain special instructions before use.
P281	Use personal protective equipment as required.
P280	Wear eye and face protection.
P308+313	IF exposed or concerned: Get medical advice/attention.
P337+313	If eye irritation persists: Get medical advice/attention.

CARLUBE DOT 4 ESP BRAKE FLUID

P405	Store locked up.
P501	Dispose of contents/container in accordance with local regulations.

SUPPLEMENTARY PRECAUTIONARY STATEMENTS

P202	Do not handle until all safety precautions have been read and understood.
P264	Wash contaminated skin thoroughly after handling.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

3 COMPOSITION/INFORMATION ON INGREDIENTS

2-(2-BUTOXYETHOXY)ETHANOL	3.0 - <5.0%
CAS-No.: 112-34-5	EC No.: 203-961-6
Classification (EC 1272/2008) Eye Irrit. 2 - H319	Classification (67/548/EEC) Xi;R36
2-(2-METHOXYETHOXY)ETHANOL	3.0 - <5.0%
CAS-No.: 111-77-3	EC No.: 203-906-6
Classification (EC 1272/2008) Repr. 2 - H361d	Classification (67/548/EEC) Repr. Cat. 3;R63
2-[2-(2-BUTOXYETHOXY)ETHOXY]ETHANOL	25.0 - <50.0%
CAS-No.: 143-22-6	EC No.: 205-592-6
Classification (EC 1272/2008) Eye Dam. 1 - H318	Classification (67/548/EEC) Xi;R41
DIETHYLENE GLYCOL	10.0 - <20.0%
CAS-No.: 111-46-6	EC No.: 203-872-2
Classification (EC 1272/2008) Acute Tox. 4 - H302	Classification (67/548/EEC) Xn;R22

The Full Text for all R-Phrases and Hazard Statements is Displayed in Section 16

The Full Text for all
R-Phrases is Displayed in
Section 16

4 FIRST-AID MEASURES

GENERAL INFORMATION

NOTE! Effects may be delayed. Keep affected person under observation. For breathing difficulties oxygen may be necessary. If breathing stops, provide artificial respiration. Get medical attention. Remove victim immediately from source of exposure. Place unconscious person on the side in the recovery position and ensure breathing can take place. Do not give victim anything to drink if they are unconscious.

CARLUBE DOT 4 ESP BRAKE FLUID

NOTES TO THE PHYSICIAN

No recommendation given, but first aid may still be required in case of accidental exposure, inhalation or ingestion of this chemical. If in doubt, GET MEDICAL ATTENTION PROMPTLY!

INHALATION

Remove victim immediately from source of exposure. Get medical attention if any discomfort continues. For breathing difficulties oxygen may be necessary. If breathing stops, provide artificial respiration. In case of inhalation of spray mist: Move person into fresh air and keep at rest. In case of persistent throat irritation or coughing: Seek medical attention and bring these instructions.

INGESTION

Get medical attention immediately! Do not give victim anything to drink if he is unconscious. Try to induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Immediately rinse mouth and drink plenty of water. If person becomes uncomfortable or if ingested in large amounts (50-100 ml for an adult person): Take to hospital along with these instructions.

SKIN CONTACT

Remove contaminated clothes and rinse skin thoroughly with water. Get medical attention if any discomfort continues.

EYE CONTACT

Do not rub eye. Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyelids widely. If irritation persists: Seek medical attention and bring along these instructions.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Use: Foam, carbon dioxide or dry powder. Use fire-extinguishing media appropriate for surrounding materials.

SPECIAL FIRE FIGHTING PROCEDURES

No specific fire fighting procedure given.

UNUSUAL FIRE & EXPLOSION HAZARDS

No unusual fire or explosion hazards noted.

PROTECTIVE MEASURES IN FIRE

Leave danger zone immediately. Use protective equipment appropriate for surrounding materials.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet. Avoid inhalation of spray mist and contact with skin and eyes. In case of spills, beware of slippery floors and surfaces.

ENVIRONMENTAL PRECAUTIONS

The product should not be dumped in nature but collected and delivered according to agreement with the local authorities. Avoid release to the environment. Avoid discharge into drains, water courses or onto the ground.

SPILL CLEAN UP METHODS

Stop leak if possible without risk. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Provide ventilation and confine spill. Do not allow runoff to sewer. Absorb spillage with suitable absorbent material.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Read and follow manufacturer's recommendations. Keep away from heat, sparks and open flame. Wear full protective clothing for prolonged exposure and/or high concentrations. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site. Do not eat, drink or smoke when using the product. Avoid inhalation of vapours/spray and contact with skin and eyes. Avoid forming spray/aerosol mists. Observe occupational exposure limits and minimise the risk of inhalation of vapours and mist. Pregnant or breastfeeding women must not handle this product. Pregnant women should not work with the product, if there is the least risk of exposure.

CARLUBE DOT 4 ESP BRAKE FLUID

STORAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Keep containers tightly closed. Keep upright. Keep in original container. Avoid contact with oxidising agents.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
2-(2-BUTOXYETHOXY)ETHANOL	WEL	10 ppm	67.5 mg/m3	15 ppm	101.2 mg/m3	
DIETHYLENE GLYCOL	WEL	23 ppm	101 mg/m3			

WEL = Workplace Exposure Limit.

PROTECTIVE EQUIPMENT



PROCESS CONDITIONS

Provide eyewash station.

ENGINEERING MEASURES

Observe occupational exposure limits and minimize the risk of inhalation of vapours. Provide adequate ventilation.

RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit.

HAND PROTECTION

Nitrile gloves are recommended. Protective gloves must be used if there is a risk of direct contact or splash.

EYE PROTECTION

Wear approved, tight fitting safety glasses where splashing is probable.

OTHER PROTECTION

Wear suitable protective clothing as protection against splashing or contamination.

HYGIENE MEASURES

Wash contaminated clothing before reuse. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid
COLOUR	Colourless. to Amber.
ODOUR	Mild.
SOLUBILITY	Miscible with water Miscible with: Ethanol.
BOILING POINT (°C)	>260°C
MELTING POINT (°C)	<-50°C
VISCOSITY	5-10 cSt 20
FLASH POINT (°C)	>100°C
AUTO IGNITION	>300°C
TEMPERATURE (°C)	

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions and recommended use.

CARLUBE DOT 4 ESP BRAKE FLUID

CONDITIONS TO AVOID

Avoid contact with: Oxidising materials.

MATERIALS TO AVOID

Strong oxidising substances.

HAZARDOUS DECOMPOSITION PRODUCTS

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

11 TOXICOLOGICAL INFORMATION

TOXIC DOSE 1 - LD 50 >5000 mg/kg (oral rat)

TOXIC DOSE 2 - LD 50 5000 (Ethanediol) mg/kg (oral-rbt)

TOXICOLOGICAL INFORMATION

No information available.

INHALATION

Unlikely to be hazardous by inhalation because of the low vapour pressure of the substance at ambient temperature. Vapours may irritate throat and respiratory system and cause coughing.

INGESTION

May cause liver and/or renal damage. Irritating. May cause nausea, stomach pain and vomiting. Harmful: possible risk of irreversible effects if swallowed.

SKIN CONTACT

Slightly irritating.

EYE CONTACT

Irritating to eyes.

HEALTH WARNINGS

May cause liver and/or renal damage. Possible reproductive impact. CNS depressant. Nephrotoxin.

ROUTE OF ENTRY

Ingestion.

TARGET ORGANS

Central nervous system Heart & cardiovascular system Kidneys

MEDICAL SYMPTOMS

Allergic rash. Delayed, often serious breathing problems. Tachycardia, (excessively rapid heart beat, including rapid and weak pulse). Unconsciousness, possibly death.

SPECIFIC EFFECTS

May cause damage to the kidneys. Contains a substance/a group of substances with possible risk of harm to the unborn child and with possible risk of impaired fertility.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

LC 50, 96 Hrs, FISH mg/l >100mg/l

BIOACCUMULATION

The product is not bioaccumulating.

DEGRADABILITY

The product is easily biodegradable.

13 DISPOSAL CONSIDERATIONS

GENERAL INFORMATION

Waste is classified as hazardous waste. Disposal to licensed waste disposal site in accordance with the local Waste Disposal Authority.

DISPOSAL METHODS

Confirm disposal procedures with environmental engineer and local regulations.

CARLUBE DOT 4 ESP BRAKE FLUID

14 TRANSPORT INFORMATION

15 REGULATORY INFORMATION

EU DIRECTIVES

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

16 OTHER INFORMATION

REVISION COMMENTS

NOTE: Lines within the margin indicate significant changes from the previous revision.

REVISION DATE 22/09/2014

REV. NO./REPL. SDS 2

GENERATED

SAFETY DATA SHEET STATUS

Approved.

RISK PHRASES IN FULL

R22 Harmful if swallowed.
R36 Irritating to eyes.
R63 Possible risk of harm to the unborn child.
R41 Risk of serious damage to eyes.

HAZARD STATEMENTS IN FULL

H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H302 Harmful if swallowed.
H361d Suspected of damaging the unborn child.