

SAFETY DATA SHEET ACTIVATED THINNER FOR ETCH PRIMER

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name ACTIVATED THINNER FOR ETCH PRIMER
Product No. GET001, GET005, GET010, GET050

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Catalystr. Additive for paint.

1.3. Details of the supplier of the safety data sheet

Manufacturer TETROSYL LIMITED
 BEVIS GREEN WORKS
 WALMERSLEY
 BURY
 BL9 6RE
 0161 764 5981
 0161 797 5899
 info@tetrosyl.com

1.4. Emergency telephone number

0161 764 5981

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical and Chemical Hazards	Flam. Liq. 2 - H225
Human health	Skin Irrit. 2 - H315; Eye Dam. 1 - H318; STOT SE 3 - H336
Environment	Not classified.

Classification (1999/45/EEC) Xi; R41. F; R11. R67.

The Full Text for all R-Phrases and Hazard Statements are Displaved in Section 16.

2.2. Label elements

Label In Accordance With (EC) No. 1272/2008



Signal Word

Danger

Hazard Statements

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H336	May cause drowsiness or dizziness.

ACTIVATED THINNER FOR ETCH PRIMER

Precautionary Statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P271	Use only outdoors or in a well-ventilated area.
P261	Avoid breathing vapour/spray.
P280	Wear protective gloves, eye and face protection.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor/physician.
P403+233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local regulations.

Supplementary Precautionary Statements

P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P264	Wash contaminated skin thoroughly after handling.
P321	Specific treatment (see medical advice on this label).
P370+378	In case of fire: Use foam, carbon dioxide, dry powder or water fog for extinction.
P302+352	IF ON SKIN: Wash with plenty of soap and water.
P303+361+353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P332+313	If skin irritation occurs: Get medical advice/attention.
P362	Take off contaminated clothing and wash before reuse.
P403+235	Store in a well-ventilated place. Keep cool.

2.3. Other hazards**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS****3.2. Mixtures**

ISO-BUTANOL	10-30%
CAS-No.: 78-83-1	EC No.: 201-148-0
Registration Number: 01-2119484609-23-XXXX	
Classification (EC 1272/2008)	Classification (67/548/EEC)
Flam. Liq. 3 - H226	R10
Skin Irrit. 2 - H315	Xi;R37/38,R41
Eye Dam. 1 - H318	R67
STOT SE 3 - H335	
STOT SE 3 - H336	

ACTIVATED THINNER FOR ETCH PRIMER

PHOSPHORIC ACID ...%	1-5%
CAS-No.: 7664-38-2	EC No.: 231-633-2
Classification (EC 1272/2008) Skin Corr. 1B - H314	Classification (67/548/EEC) C;R34
PROPAN-1-OL	60-100%
CAS-No.: 71-23-8	EC No.: 200-746-9
Classification (EC 1272/2008) Flam. Liq. 2 - H225 Eye Dam. 1 - H318 STOT SE 3 - H336	Classification (67/548/EEC) F;R11 Xi;R41 R67

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General information

Remove affected person from source of contamination. NOTE! Effects may be delayed. Keep affected person under observation. Get medical attention. CAUTION! First aid personnel must be aware of own risk during rescue! Move the exposed person to fresh air at once. NOTE! Keep affected person away from heat, sparks and flames! Perform artificial respiration if breathing has stopped. Place unconscious person on the side in the recovery position and ensure breathing can take place.

Inhalation

Remove victim immediately from source of exposure. Move injured person into fresh air and keep person calm under observation. If uncomfortable: Seek hospital and bring these instructions. Place unconscious person on the side in the recovery position and ensure breathing can take place. Perform artificial respiration if breathing has stopped.

Ingestion

Get medical attention immediately! Immediately rinse mouth and drink plenty of water or milk. Keep person under observation. Do not induce vomiting. If vomiting occurs, keep head low. Transport immediately to hospital and bring along these instructions. Do not give victim anything to drink if he is unconscious. NOTE! Keep affected person away from heat, sparks and flames! When risk of unconsciousness, place and transport the victim in secured side position.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. Rinse with water. Use suitable lotion to moisturise skin. Get medical attention promptly if symptoms occur after washing.

Eye contact

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Do not rub eye. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

General information

The severity of the symptoms described will vary dependant of the concentration and the length of exposure. NOTE! Effects may be delayed. Keep affected person under observation.

ACTIVATED THINNER FOR ETCH PRIMER

Inhalation

In case of overexposure, organic solvents may depress the central nervous system causing dizziness and intoxication, and at very high concentrations unconsciousness and death. Vapours may cause headache, fatigue, dizziness and nausea. In high concentrations, vapours are anaesthetic and may cause headache, fatigue, dizziness and central nervous system effects.

Ingestion

May cause discomfort if swallowed. May cause stomach pain or vomiting. May cause nausea, headache, dizziness and intoxication. May cause chemical burns in mouth and throat. Central nervous system depression. Fumes from the stomach contents may be inhaled resulting in the same symptoms as inhalation.

Skin contact

Prolonged contact may cause redness, irritation and dry skin.

Eye contact

Irritation, burning, lachrymation, blurred vision after liquid splash.

4.3. Indication of any immediate medical attention and special treatment needed

No recommendation given, but first aid may still be required in case of accidental exposure, inhalation or ingestion of this chemical. If in doubt, GET MEDICAL ATTENTION PROMPTLY!

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media

Use: Foam, carbon dioxide or dry powder. Water. Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

Unusual Fire & Explosion Hazards

HIGHLY FLAMMABLE! Forms explosive mixtures with air. Vapours are heavier than air and may spread near ground to sources of ignition. May travel considerable distance to source of ignition and flash back.

Specific hazards

Vapours may form explosive air mixtures even at room temperature. Vapours are heavier than air and may travel along the floor and in the bottom of containers. Vapours may be ignited by a spark, a hot surface or an ember.

5.3. Advice for firefighters

Special Fire Fighting Procedures

Avoid breathing fire vapours. Keep up-wind to avoid fumes. Be aware of risk of fire re-starting, and risk of explosion. Cool containers exposed to flames with water until well after the fire is out. Use water SPRAY only to cool containers! Do not put water on leaked material.

Protective equipment for fire-fighters

Leave danger zone immediately.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Wear protective clothing as described in Section 8 of this safety data sheet. In case of inadequate ventilation, use respiratory protection. Take precautionary measures against static discharges. Do not smoke, use open fire or other sources of ignition. Do not breathe vapour. Avoid contact with skin and eyes. In case of spills, beware of slippery floors and surfaces.

6.2. Environmental precautions

ACTIVATED THINNER FOR ETCH PRIMER

Do not discharge into drains, water courses or onto the ground. Prevent entry into drains. Avoid discharge to the aquatic environment.

6.3. Methods and material for containment and cleaning up

For waste disposal, see section 13. Stop leak if possible without risk. Collect with absorbent, non-combustible material into suitable containers. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Provide ventilation and confine spill. Do not allow runoff to sewer. Cover large spillages with alcohol-resistant foam.

6.4. Reference to other sections

Wear protective clothing as described in Section 8 of this safety data sheet. For waste disposal, see section 13.

SECTION 7: HANDLING AND STORAGE**7.1. Precautions for safe handling**

Read and follow manufacturer's recommendations. Eliminate all sources of ignition. Keep away from heat, sparks and open flame. Risk of vapour concentration on the floor and in low-lying areas. Static electricity and formation of sparks must be prevented. Do not eat, drink or smoke when using the product. Avoid inhalation of vapours/spray and contact with skin and eyes. Observe good chemical hygiene practices. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Mechanical ventilation or local exhaust ventilation may be required.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Keep containers tightly closed. Keep upright. Keep in original container. Avoid contact with oxidising agents. Do not store near heat sources or expose to high temperatures. Store separated from: Oxidising material.

Storage Class

Flammable liquid storage.

7.3. Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1. Control parameters**

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
ISO-BUTANOL	WEL	50 ppm	154 mg/m ³	75 ppm	231 mg/m ³	
PHOSPHORIC ACID ...%	WEL		1 mg/m ³		2 mg/m ³	
PROPAN-1-OL	WEL	200 ppm(Sk)	500 mg/m ³ (Sk)	250 ppm(Sk)	625 mg/m ³ (Sk)	

WEL = Workplace Exposure Limit.

8.2. Exposure controls

Protective equipment



ACTIVATED THINNER FOR ETCH PRIMER

Process conditions

Provide eyewash station.

Engineering measures

Provide explosion proof ventilation for high concentrations. Observe occupational exposure limits and minimize the risk of inhalation of vapours. All handling to take place in well-ventilated area.

Respiratory equipment

If ventilation is insufficient, suitable respiratory protection must be provided. Check that mask fits tight and change filter regularly. Use respiratory equipment with gas filter, type AX.

Hand protection

For prolonged or repeated skin contact use suitable protective gloves. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material. Be aware that the liquid may penetrate the gloves. Frequent change is advisable.

Eye protection

Wear approved, tight fitting safety glasses where splashing is probable.

Other Protection

Wear suitable protective clothing as protection against splashing or contamination.

Hygiene measures

Wash promptly with soap & water if skin becomes contaminated. When using do not eat, drink or smoke.

Isolate contaminated clothing and wash before reuse.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance	Clear liquid.
Colour	Colourless.
Odour	of solvents
Solubility	Miscible with water
Initial boiling point and boiling range (°C)	97°C
Melting point (°C)	Not determined.
Relative density	0.820 - 0.830 20
Vapour density (air=1)	Not determined.
Vapour pressure	Not determined.
Evaporation rate	Not determined.
Viscosity	<50 cP 20°C
Decomposition temperature (°C)	Not determined.
Odour Threshold, Lower	Not determined.
Odour Threshold, Upper	Not determined.
Flash point (°C)	23°C
Auto Ignition Temperature (°C)	Not determined.

ACTIVATED THINNER FOR ETCH PRIMER

Flammability Limit - Lower(%)

Not determined.

Flammability Limit - Upper(%)

Not determined.

Partition Coefficient

(N-Octanol/Water)

Not determined.

Oxidising properties

Not available.

9.2. Other information

None.

SECTION 10: STABILITY AND REACTIVITY**10.1. Reactivity**

The product may form explosive vapours/air mixtures even at normal room temperatures.

10.2. Chemical stability

Stable under normal temperature conditions and recommended use.

10.3. Possibility of hazardous reactions

Not relevant

10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition. Avoid exposure to high temperatures or direct sunlight.

10.5. Incompatible materials

Materials To Avoid

Strong oxidising substances.

10.6. Hazardous decomposition products

None at ambient temperatures. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

SECTION 11: TOXICOLOGICAL INFORMATION**11.1. Information on toxicological effects**

Toxic Dose 1 - LD 50

6800 mg/kg (oral-mouse)

Toxic Dose 2 - LD 50

2825 mg/kg (oral-rbt)

Acute toxicity:

Propan-1-OL

General information

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

Contains small amounts of organic solvents. Extensive use of the product in areas with inadequate ventilation may result in hazardous vapour concentrations.

ACTIVATED THINNER FOR ETCH PRIMER**Inhalation**

Vapours may irritate throat and respiratory system and cause headache, dizziness and dullness. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia. Contains organic solvents which in case of overexposure may depress the central nervous system causing dizziness and intoxication.

Ingestion

May cause internal injury. May cause nausea, headache, dizziness and intoxication. Harmful: may cause lung damage if swallowed. Pneumonia may be the result if vomited material containing solvents reaches the lungs.

Skin contact

Prolonged contact may cause dryness of the skin. Repeated exposure may cause skin dryness or cracking.

Eye contact

Irritating and may cause redness and pain. Spray and vapour in the eyes may cause irritation and smarting.

Health Warnings

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

Route of entry

Inhalation. Skin absorption. Ingestion. Skin and/or eye contact.

Medical Symptoms

Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo.

Medical Considerations

Risk of chemical pneumonia after aspiration.

SECTION 12: ECOLOGICAL INFORMATION**Ecotoxicity**

Dangerous for the environment if discharged into watercourses.

12.1. Toxicity

LC 50, 96 Hrs, Fish mg/l 4480

Propan-1-OL

EC 50, 48 Hrs, Daphnia, mg/l 3642

12.2. Persistence and degradability**Degradability**

There are no data on the degradability of this product.

12.3. Bioaccumulative potential**Bioaccumulative potential**

No data available on bioaccumulation.

Partition coefficient

Not determined.

12.4. Mobility in soil**Adsorption/Desorption Coefficient**

Not available.

12.5. Results of PBT and vPvB assessment

Not Classified as PBT/vPvB by current EU criteria.

12.6. Other adverse effects

Not available.

ACTIVATED THINNER FOR ETCH PRIMER**SECTION 13: DISPOSAL CONSIDERATIONS**

General information

Waste is classified as hazardous waste. Disposal to licensed waste disposal site in accordance with the local Waste Disposal Authority. Do not puncture or incinerate even when empty.

13.1. Waste treatment methods

Confirm disposal procedures with environmental engineer and local regulations. Make sure containers are empty before discarding (explosion risk). Empty containers must not be burned because of explosion hazard. Recover and reclaim or recycle, if practical.

SECTION 14: TRANSPORT INFORMATION**14.1. UN number**

UN No. (ADR/RID/ADN)	1263
UN No. (IMDG)	1263
UN No. (ICAO)	1263

14.2. UN proper shipping name

Proper Shipping Name PAINT RELATED MATERIAL

14.3. Transport hazard class(es)

ADR/RID/ADN Class	3
ADR/RID/ADN Class	Class 3: Flammable liquids.
ADR Label No.	3
IMDG Class	3
ICAO Class/Division	3
Transport Labels	

**14.4. Packing group**

ADR/RID/ADN Packing group	II
IMDG Packing group	II
ICAO Packing group	II

14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant
No.

14.6. Special precautions for user

EMS	F-E, S-E
Emergency Action Code	3YE
Hazard No. (ADR)	33

ACTIVATED THINNER FOR ETCH PRIMER**14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code****SECTION 15: REGULATORY INFORMATION****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

EU Legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

15.2. Chemical Safety Assessment

No chemical safety assessment has been carried out.

SECTION 16: OTHER INFORMATION

Revision Comments

NOTE: Lines within the margin indicate significant changes from the previous revision.

Issued By	Health & Safety Department
Revision Date	06/07/2011
Revision	8
Supersedes date	17/12/2007 v7
Safety Data Sheet Status	Approved.
Risk Phrases In Full	
R34	Causes burns.
R10	Flammable
R11	Highly flammable
R37/38	Irritating to respiratory system and skin.
R41	Risk of serious damage to eyes.
R67	Vapours may cause drowsiness and dizziness.
Hazard Statements In Full	
H318	Causes serious eye damage.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H226	Flammable liquid and vapour.
H225	Highly flammable liquid and vapour.
H336	May cause drowsiness or dizziness.
H335	May cause respiratory irritation.