

# SAFETY DATA SHEET CARLUBE S/S ENGINE CLEANER PETROL

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name CARLUBE S/S ENGINE CLEANER PETROL

Product number QPS300

1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Fuel additive.

1.3. Details of the supplier of the safety data sheet

Supplier TETROSYL LIMITED

Bury Lancashire England BL9 7NY 0161 764 5981 0161 797 5899 info@tetrosyl.com

Manufacturer TETROSYL LIMITED

Bury Lancashire England BL9 7NY 0161 764 5981 0161 797 5899 info@tetrosyl.com

1.4. Emergency telephone number

**Emergency telephone** +44 (0)161 764 5981

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

**Health hazards** Asp. Tox. 1 - H304

Environmental hazards Not Classified

2.2. Label elements

Hazard pictograms



Signal word Danger

# **CARLUBE S/S ENGINE CLEANER PETROL**

**Hazard statements** H304 May be fatal if swallowed and enters airways.

Precautionary statements P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P405 Store locked up.

P501 Dispose of contents/ container in accordance with national regulations.

Contains DISTILLATES (PETROLEUM), HYDROTREATED LIGHT; KEROSINE - UNSPECIFIED,

HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

#### 2.3. Other hazards

Not applicable.

#### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT;

60-100%

**KEROSINE - UNSPECIFIED** 

CAS number: — EC number: 926-141-6 REACH registration number: 01-

2119484819-18-0001

Classification

Asp. Tox. 1 - H304

# HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES,

3-<5.0%

CYCLICS, <2% AROMATICS

CAS number: — EC number: 918-481-9

#### Classification

Flam. Liq. 3 - H226 Asp. Tox. 1 - H304

# PHENOL, (DIMETHYLAMINO)METHYL-

3-<5.0%

,POLYISOBUTYLENE DERIVS.

CAS number: —

#### Classification

Aquatic Chronic 3 - H412

NAPHTHALENE -<0.05

#### Classification

Flam. Sol. 2 - H228 Acute Tox. 4 - H302 Carc. 2 - H351

Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410

#### CARLUBE S/S ENGINE CLEANER PETROL

The full text for all hazard statements is displayed in Section 16.

#### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

General information Remove affected person from source of contamination. Keep the affected person warm and at

rest. Get prompt medical attention.

Inhalation Get medical attention if any discomfort continues. Move affected person to fresh air and keep

> warm and at rest in a position comfortable for breathing. Get medical attention. Symptoms of lung oedema (shortness of breath) may develop up to 24 hours after exposure. Show this

Safety Data Sheet to the medical personnel.

Ingestion Rinse mouth thoroughly with water. Give plenty of water to drink. Get medical attention if a

large quantity has been ingested. Show this Safety Data Sheet to the medical personnel.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. Rinse with

water. Get medical attention if irritation persists after washing.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide

apart. Continue to rinse for at least 15 minutes. Do not rub eye. Get medical attention

promptly if symptoms occur after washing.

#### 4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure. Effects may be delayed. Keep affected person under observation.

Inhalation No specific symptoms known.

Ingestion May cause discomfort if swallowed. May cause stomach pain or vomiting.

Skin contact Skin irritation. Prolonged or repeated contact with skin may cause irritation, redness and

dermatitis. Blistering may occur.

Eye contact Irritating to eyes. Symptoms following overexposure may include the following: Redness.

Pain. May cause blurred vision and serious eye damage.

### 4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations. If in doubt, get medical attention promptly.

#### SECTION 5: Firefighting measures

## 5.1. Extinguishing media

Extinguish with the following media: Foam, carbon dioxide or dry powder. Water. Use fire-Suitable extinguishing media

extinguishing media suitable for the surrounding fire.

#### 5.2. Special hazards arising from the substance or mixture

Specific hazards No specific precautions due to the small quantities handled. No unusual fire or explosion

hazards noted.

Hazardous combustion

Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and

other toxic gases or vapours.

5.3. Advice for firefighters

Protective actions during

firefighting

products

No specific firefighting precautions known.

Special protective equipment

for firefighters

Leave danger zone immediately.

#### SECTION 6: Accidental release measures

#### CARLUBE S/S ENGINE CLEANER PETROL

#### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions For personal protection, see Section 8. In case of spills, beware of slippery floors and

surfaces. Avoid contact with eyes and prolonged skin contact. Provide adequate ventilation.

Avoid inhalation of spray mist and contact with skin and eyes.

#### 6.2. Environmental precautions

**Environmental precautions** Avoid discharge into drains or watercourses or onto the ground. Collect and dispose of

spillage as indicated in Section 13.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if possible without risk. Eliminate all sources of ignition. No smoking, sparks, flames

or other sources of ignition near spillage. Provide adequate ventilation. Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers

and seal securely.

#### 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8. For waste disposal, see section 13.

#### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Usage precautions Good personal hygiene procedures should be implemented. Wash hands and any other

contaminated areas of the body with soap and water before leaving the work site. Avoid eating, drinking and smoking when using the product. Avoid contact with skin and eyes. Do

not handle broken packages without protective equipment.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep containers upright. Store in tightly-closed, original container. Keep away from heat,

sparks and open flame.

#### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

#### SECTION 8: Exposure controls/Personal protection

#### 8.1. Control parameters

#### Occupational exposure limits

No exposure limits known for ingredient(s).

#### **NAPHTHALENE**

Long-term exposure limit (8-hour TWA): 10 53 Short-term exposure limit (15-minute): 15 80

#### 8.2. Exposure controls

#### Protective equipment





Appropriate engineering

controls

Provide adequate ventilation. Avoid inhalation of vapours and spray/mists. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.

#### CARLUBE S/S ENGINE CLEANER PETROL

Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be worn if

a risk assessment indicates skin contact is possible. It is recommended that gloves are made of the following material: Nitrile rubber. It should be noted that liquid may penetrate the gloves.

Frequent changes are recommended.

Other skin and body

protection

Wear appropriate clothing to prevent any possibility of skin contact. Provide eyewash station.

Hygiene measures Provide eyewash station and safety shower. Wash contaminated clothing before reuse. Wash

promptly with soap and water if skin becomes contaminated.

**Respiratory protection** If ventilation is inadequate, suitable respiratory protection must be worn.

#### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

**Appearance** Clear liquid.

Colour Yellow.

Odour Organic solvents.

Melting point Not determined.

Initial boiling point and range 175°C @

Flash point 75°C

**Evaporation rate** Not determined.

Upper/lower flammability or

explosive limits

Not determined.

Vapour pressure Not determined.

Vapour density Not determined.

Relative density 0.805g/cm³ @ 20°C

Solubility(ies) Insoluble in water.

Partition coefficient Not determined.

Auto-ignition temperature Not determined.

**Decomposition Temperature** Not determined.

Viscosity <50 cP @ 20°C

9.2. Other information

Other information None.

#### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

**Reactivity** The following materials may react strongly with the product: Alkaline earth metals. Powdered

metal.

10.2. Chemical stability

**Stability** No particular stability concerns.

#### 10.3. Possibility of hazardous reactions

#### CARLUBE S/S ENGINE CLEANER PETROL

Possibility of hazardous

reactions

Not applicable.

10.4. Conditions to avoid

Conditions to avoid Avoid heat. Avoid contact with the following materials: Strong oxidising agents.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition

products

Does not decompose when used and stored as recommended.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

**Toxicological effects** No information available.

**Inhalation** Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause

chemical pneumonitis.

Medical considerations Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause

chemical pneumonitis.

SECTION 12: Ecological information

**Ecotoxicity**The product contains a substance which is harmful to aquatic organisms and which may

cause long-term adverse effects in the aquatic environment.

12.1. Toxicity

Acute aquatic toxicity

Acute toxicity - fish LC<sub>50</sub>, 96 hours: 2200 (DISTILLATES (PETROLEUM), HYDROTREATED LIGHT; KEROSINE

- UNSPECIFIED) mg/l, Fish

Acute toxicity - aquatic

invertebrates

Not available.

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not determined.

12.4. Mobility in soil

Adsorption/desorption

Not available.

coefficient

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects Not applicable.

#### CARLUBE S/S ENGINE CLEANER PETROL

#### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

General information Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site

in accordance with the requirements of the local Waste Disposal Authority.

**Disposal methods**Dispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority. Confirm disposal procedures with environmental engineer and

local regulations.

#### SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods

(IMDG, IATA, ADR/RID).

#### 14.1. UN number

Not applicable.

#### 14.2. UN proper shipping name

Not applicable.

#### 14.3. Transport hazard class(es)

No transport warning sign required.

#### 14.4. Packing group

Not applicable.

#### 14.5. Environmental hazards

#### Environmentally hazardous substance/marine pollutant

No.

#### 14.6. Special precautions for user

Not applicable.

#### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

#### SECTION 15: Regulatory information

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations EH40/2005 Workplace exposure limits.

**EU legislation** Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18

December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

#### SECTION 16: Other information

**Revision comments** NOTE: Lines within the margin indicate significant changes from the previous revision.

Issued by Health & Safety Department

# **CARLUBE S/S ENGINE CLEANER PETROL**

Revision date 01/07/2019

Revision 1

SDS number 33281

SDS status Approved.

Hazard statements in full H226 Flammable liquid and vapour.

H228 Flammable solid. H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H351 Suspected of causing cancer. H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.