Report Date: 28/04/2014 Revision Date 28/04/2014 Revision 23

Revision 23

Supersedes date 18/12/2012 v22



SAFETY DATA SHEET Masonry Repair Filler

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE **COMPANY/UNDERTAKING**

1.1. Product identifier

Product name Masonry Repair Filler Product No. TSF200, TSF500, BDM001

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Household Maintenance Product

1.3. Details of the supplier of the safety data sheet

Supplier TETROSYL LIMITED

BEVIS GREEN WORKS

WALMERSLEY

BURY

BL9 6RE

0161 764 5981 0161 797 5899

info@tetrosyl.com

Manufacturer TETROSYL LIMITED

BEVIS GREEN WORKS

WALMERSLEY

BURY

BL9 6RE

0161 764 5981 0161 797 5899

info@tetrosyl.com

1.4. Emergency telephone number

0161 764 5981

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical and Chemical Not classified.

Hazards

Human health Skin Irrit. 2 - H315; Eye Dam. 1 - H318

Not classified. Environment

Classification (1999/45/EEC) Xi;R36/38.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

2.2. Label elements

Label In Accordance With (EC) No. 1272/2008

Report Date : 28/04/2014 2 / 7
Revision 23

Masonry Repair Filler



Signal Word Danger

Hazard Statements

H315 Causes skin irritation.

H318 Causes serious eye damage.

Precautionary Statements

P101 If medical advice is needed, have product container or label

at hand.

P102 Keep out of reach of children.

P280 Wear protective gloves/protective clothing/eye protection/face

protection.

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue

rinsing.

P337+313 If eye irritation persists: Get medical advice/attention.

Supplementary Precautionary Statements

P264 Wash contaminated skin thoroughly after handling.
P321 Specific treatment (see medical advice on this label).
P302+352 IF ON SKIN: Wash with plenty of soap and water.

P310 Immediately call a POISON CENTER or doctor/physician.
P332+313 If skin irritation occurs: Get medical advice/attention.
P362 Take off contaminated clothing and wash before reuse.

2.3. Other hazards

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

CALCIUM ALUMINATE 25.0 - <50.0%

CAS-No.: 65997-16-2 EC No.:

Classification (EC 1272/2008) Classification (67/548/EEC)

Not classified. Xi;R36/38.

CALCIUM FORMATE 3.0 - <5.0%

CAS-No.: 544-17-2 EC No.:

Classification (EC 1272/2008) Classification (67/548/EEC)

Not classified. Xi;R36/37/38.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

Report Date: 28/04/2014 3 / 7
Revision: 23

Masonry Repair Filler

General information

Remove affected person from source of contamination. NOTE! Effects may be delayed. Keep affected person under observation. General first aid, rest, warmth and fresh air. Get medical attention if any discomfort continues.

Inhalation

Remove victim immediately from source of exposure. Get medical attention if any discomfort continues.

Ingestion

Rinse mouth thoroughly. Drink plenty of water. Get medical attention if any discomfort continues.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. Rinse with water. Get medical attention if any discomfort continues.

Eye contact

Important! Immediately rinse with water for at least 15 minutes. Make sure to remove any contact lenses from the eyes before rinsing. Get medical attention promptly if symptoms occur after washing.

4.2. Most important symptoms and effects, both acute and delayed

General information

The severity of the symptoms described will vary dependant of the concentration and the length of exposure. NOTE! Effects may be delayed. Keep affected person under observation.

Inhalation

May cause an asthma-like shortness of breath. Upper respiratory irritation. Inhalation of dusts during cutting, grinding or sanding of this product may cause irritation of the respiratory tract.

Ingestion

May cause discomfort if swallowed. May cause stomach pain or vomiting. May cause chemical burns in mouth and throat. Metallic taste.

Skin contact

Skin irritation. Prolonged or repeated contact with skin may cause redness, itching, irritation and eczema/chapping. Blistering may occur. Burns can occur.

Eye contact

Irritating and may cause redness and pain. May cause blurred vision and serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

No recommendation given, but first aid may still be required in case of accidental exposure, inhalation or ingestion of this chemical. If in doubt, GET MEDICAL ATTENTION PROMPTLY!

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media

Use: Foam, carbon dioxide or dry powder. Water. Use fire-extinguishing media appropriate for surrounding materials.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products

There are no anticipated hazardous decomposition products associated with this material.

Unusual Fire & Explosion Hazards

No unusual fire or explosion hazards noted.

5.3. Advice for firefighters

Special Fire Fighting Procedures

No specific fire fighting procedure given.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Report Date: 28/04/2014 4 / 7

Revision 23

Masonry Repair Filler

For personal protection, see section 8. Avoid contact with skin and eyes. Avoid inhalation of dust.

6.2. Environmental precautions

Avoid discharge into water courses or onto the ground. The product should not be dumped in nature but collected and delivered according to agreement with the local authorities.

6.3. Methods and material for containment and cleaning up

Avoid generation and spreading of dust. Remove small spills with vacuum cleaner.

6.4. Reference to other sections

For personal protection, see section 8. For waste disposal, see section 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site. Avoid eating, drinking and smoking when using the product. Avoid handling which leads to dust formation. Avoid inhalation of dust and contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

No specific recommendations.

7.3. Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

8.2. Exposure controls

Protective equipment







Engineering measures

Provide adequate ventilation. Observe occupational exposure limits and minimize the risk of inhalation of dust. Respiratory equipment

If ventilation is insufficient, suitable respiratory protection must be provided. Use respiratory equipment with particle filter, type P2.

Hand protection

Use suitable protective gloves if risk of skin contact. Nitrile gloves are recommended.

Eye protection

Wear dust resistant safety goggles where there is danger of eye contact.

Other Protection

Provide eyewash station.

Hygiene measures

When using do not eat, drink or smoke. Wash hands after contact. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Wash contaminated clothing before reuse.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Report Date: 28/04/2014 5 / 7

Masonry Repair Filler

Revision 23

Appearance Powder, dust

Colour Grey.
Odour Odourless.
Solubility Soluble in water.

Initial boiling point and boiling range (°C)

Scientifically unjustified. Melting point (°C) Not determined.

Relative density 1.1 20°C

Vapour density (air=1) Not determined. Vapour pressure Not determined.

Evaporation rate Not determined.

Decomposition temperature (°C)

Not determined.

Odour Threshold, Lower

Not determined.

Odour Threshold, Upper

Not determined.

Auto Ignition Temperature (°C)

Not determined.

Flammability Limit - Lower(%)

Not determined.

Flammability Limit - Upper(%)

Not determined. Partition Coefficient (N-Octanol/Water)

Not determined.

Oxidising properties

Not available.

9.2. Other information

None.

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

The product reacts with water and will generate heat.

10.2. Chemical stability

No particular stability concerns. The substance is hygroscopic and will absorb water by contact with the moisture in the air.

10.3. Possibility of hazardous reactions

Not applicable.

10.4. Conditions to avoid

No specific conditions are likely to result in a hazardous situation.

10.5. Incompatible materials

Materials To Avoid

No incompatible groups noted.

Report Date: 28/04/2014 6 / 7
Revision: 23

Masonry Repair Filler

10.6. Hazardous decomposition products

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Toxicological information

No information available.

Health Warnings

This chemical may cause skin/eye irritation. Dust may irritate respiratory system.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

Dangerous for the environment if discharged into watercourses.

12.1. Toxicity

Acute Toxicity - Fish

Not available.

Acute Toxicity - Aquatic Invertebrates

Not available.

12.2. Persistence and degradability

Degradability

There are no data on the degradability of this product.

12.3. Bioaccumulative potential

Bioaccumulative potential

No data available on bioaccumulation.

Partition coefficient

Not determined.

12.4. Mobility in soil

Adsorption/Desorption Coefficient

Not available.

12.5. Results of PBT and vPvB assessment

Not Classified as PBT/vPvB by current EU criteria.

12.6. Other adverse effects

Not applicable.

SECTION 13: DISPOSAL CONSIDERATIONS

General information

Waste to be treated as controlled waste. Disposal to licensed waste disposal site in accordance with local Waste Disposal Authority.

13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements. Confirm disposal procedures with environmental engineer and local regulations.

SECTION 14: TRANSPORT INFORMATION

14.1. UN number

Report Date : 28/04/2014 7 / 7
Revision 23

Masonry Repair Filler

14.2. UN proper shipping name

Proper Shipping Name N/A

14.3. Transport hazard class(es)

ADR/RID/ADN Class N/A.
IMDG Class N/A

14.4. Packing group

IMDG Packing group N/A

14.5. Environmental hazards

14.6. Special precautions for user

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

15.2. Chemical Safety Assessment

No chemical safety assessment has been carried out.

SECTION 16: OTHER INFORMATION

Revision Comments

NOTE: Lines within the margin indicate significant changes from the previous revision.

Revision Date 28/04/2014

Revision 23

Supersedes date 18/12/2012 v22 Safety Data Sheet Status Approved.

Risk Phrases In Full

R36/38 Irritating to eyes and skin.

R36/37/38 Irritating to eyes, respiratory system and skin.

Hazard Statements In Full

H318 Causes serious eye damage.

H315 Causes skin irritation.