

SAFETY DATA SHEET A-WONDER TYRE AND TRIM

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name A-WONDER TYRE AND TRIM

Product number WTS053

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Paint. Car maintenance product.

1.3. Details of the supplier of the safety data sheet

Supplier TETROSYL LIMITED

Bury Lancashire England BL9 7NY 0161 764 5981 0161 797 5899 info@tetrosyl.com

Manufacturer TETROSYL LIMITED

Bury Lancashire England BL9 7NY 0161 764 5981 0161 797 5899 info@tetrosyl.com

1.4. Emergency telephone number

Emergency telephone +44 (0)161 764 5981

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Aerosol 1 - H222, H229

Health hazards Skin Irrit. 2 - H315 STOT SE 3 - H336

Environmental hazards Aquatic Chronic 2 - H411

2.2. Label elements

Hazard pictograms







Signal word

Danger

Hazard statements H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing spray.

P264 Wash contaminated skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTRE/doctor if you feel unwell.

P332+P313 If skin irritation occurs: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse.

P391 Collect spillage.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P501 Dispose of contents/ container in accordance with national regulations.

Contains HYDROCARBONS, C7, N-ALKANES, ISOALKANES, CYCLICS (<0.1% BENZENE

CONTENT), IPA

Detergent labelling ≥ 30% aliphatic hydrocarbons

statements

Supplementary precautionary P321 Specific treatment (see medical advice on this label).

2.3. Other hazards

This substance is not classified as PBT or vPvB according to current EU criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

HYDROCARBONS, C7, N-ALKANES, ISOALKANES,

30-<60%

CYCLICS (<0.1% BENZENE CONTENT)

CAS number: -EC number: 927-510-4 REACH registration number: 01-

2119475515-33-XXXX

Classification

Flam. Liq. 2 - H225

Skin Irrit. 2 - H315

STOT SE 3 - H336

Asp. Tox. 1 - H304

Aquatic Chronic 2 - H411

PETROLEUM GASES, LIQUEFIED 30-<60%

Classification Flam. Gas 1 - H220

IPA 3-<5.0%

CAS number: 67-63-0 EC number: 200-661-7 REACH registration number: 01-

2119457558-25-0000

Classification

Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Get medical attention if any discomfort continues. Remove affected person from source of

contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Effects may be delayed. Keep affected person under observation.

Inhalation Remove affected person from source of contamination. If spray/mist has been inhaled,

proceed as follows. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Keep affected person under observation. Get medical attention. Show this Safety Data Sheet to the medical personnel. Symptoms of lung oedema (shortness of breath) may develop up to 24 hours after exposure. Get medical attention

immediately.

Ingestion Rinse mouth thoroughly with water. Give plenty of water to drink. Keep affected person under

observation. Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical personnel. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Do not induce vomiting. If vomiting occurs, the head should

be kept low so that vomit does not enter the lungs.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. Consult a

physician for specific advice.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide

apart. Continue to rinse for at least 15 minutes. Do not rub eye. Get medical attention

promptly if symptoms occur after washing.

4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure. Effects may be delayed. Keep affected person under observation.

Inhalation May cause an asthma-like shortness of breath. In case of overexposure, organic solvents may

depress the central nervous system causing dizziness and intoxication, and at very high concentrations unconsciousness and death. Drowsiness, dizziness, disorientation, vertigo.

Vapours may cause drowsiness and dizziness. Vapours in high concentrations are

anaesthetic. Symptoms following overexposure may include the following: Headache. Fatigue.

Dizziness. Central nervous system depression.

Revision date: 17/04/2019 Revision: 9 Supersedes date: 05/04/2016

A-WONDER TYRE AND TRIM

Ingestion May cause discomfort if swallowed. May cause stomach pain or vomiting. May cause nausea,

headache, dizziness and intoxication. Due to the physical nature of this material it is unlikely

that swallowing will occur.

Skin contact Prolonged contact may cause redness, irritation and dry skin. May cause skin

irritation/eczema.

Eye contact Severe irritation, burning and tearing. Vapour, spray or dust may cause chronic eye irritation

or eye damage. May cause blurred vision and serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations. If in doubt, get medical attention promptly.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with the following media: Foam, carbon dioxide or dry powder. Water spray. Use

fire-extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up.

Vapours may be ignited by a spark, a hot surface or an ember. Vapours may form explosive mixtures with air. Extremely flammable. Severe explosion hazard when vapours are exposed to flames. Risk of explosion if heated. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. Containers can burst violently or explode when heated, due to excessive pressure build-up. Containers can burst violently or explode when heated, due to

excessive pressure build-up.

Hazardous combustion products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Oxides of carbon. Oxides of nitrogen. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Oxides of carbon. Oxides of nitrogen.

5.3. Advice for firefighters

Protective actions during firefighting

Risk of re-ignition after fire has been extinguished. Risk of explosion. Cool containers exposed to flames with water until well after the fire is out. Use water to keep fire exposed containers

cool and disperse vapours.

Special protective equipment for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. Avoid inhalation

of vapours. In case of spills, beware of slippery floors and surfaces.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground. Collect and dispose of

spillage as indicated in Section 13.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

For waste disposal, see Section 13. If leakage cannot be stopped, evacuate area. Stop leak if possible without risk. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely.

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet. For waste

disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Read and follow manufacturer's recommendations. Eliminate all sources of ignition. Wear suitable protective equipment for prolonged exposure and/or high concentrations of vapours, spray or mist. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Do not eat, drink or smoke when using the product. Avoid inhalation of vapours/spray and contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level. Do not use in confined spaces without adequate ventilation and/or respirator. Mechanical ventilation or local exhaust ventilation may be required. Observe any occupational exposure limits for the product or ingredients. Avoid inhalation of vapours and spray/mists.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep away from heat, sparks a

Keep away from heat, sparks and open flame. Keep containers upright. Protect against physical damage and/or friction. Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C. Do not store for long periods. Do not store in large quantities. Store in a cool and well-ventilated place. Keep container dry. Do not store near heat sources or expose to high temperatures.

Storage class

Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

No exposure limits known for ingredient(s).

PETROLEUM GASES, LIQUEFIED

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m³ Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m³ Carc

IPA

Long-term exposure limit (8-hour TWA): WEL 400 ppm 999 mg/m³ Short-term exposure limit (15-minute): WEL 500 ppm 1250 mg/m³

WEL = Workplace Exposure Limit

Carc = Capable of causing cancer and/or heritable genetic damage.

8.2. Exposure controls

Protective equipment











Appropriate engineering

controls

Provide adequate ventilation. Avoid inhalation of vapours and spray/mists. Observe any occupational exposure limits for the product or ingredients. Use explosion-proof general and

local exhaust ventilation.

Eye/face protection Eyewear complying with an approved standard should be worn if a risk assessment indicates

eye contact is possible. Unless the assessment indicates a higher degree of protection is

required, the following protection should be worn: Tight-fitting safety glasses.

Hand protection No specific hand protection recommended. Chemical-resistant, impervious gloves complying

with an approved standard should be worn if a risk assessment indicates skin contact is

possible.

Other skin and body

protection

Provide eyewash station. Wear appropriate clothing to prevent repeated or prolonged skin

contact.

Hygiene measures Wash contaminated clothing before reuse. Wash at the end of each work shift and before

eating, smoking and using the toilet. Promptly remove any clothing that becomes

contaminated. Wash promptly with soap and water if skin becomes contaminated. Do not

smoke in work area. When using do not eat, drink or smoke.

Respiratory protection If ventilation is inadequate, suitable respiratory protection must be worn.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Clear liquid. Colour Colourless. Odour Solvent.

Odour threshold Not determined. Not determined.

pН Not determined.

Initial boiling point and range Technically not feasible.

-12°C Flash point

Evaporation rate Not determined.

Upper/lower flammability or

explosive limits

Melting point

Not determined.

Not determined.

Not determined. Vapour pressure Vapour density Not determined. 0.730 @ °C Relative density

Solubility(ies) Immiscible with water.

Partition coefficient Not determined. **Auto-ignition temperature** Not determined. **Decomposition Temperature** Not determined. Revision date: 17/04/2019 Revision: 9 Supersedes date: 05/04/2016

A-WONDER TYRE AND TRIM

<50 cP @ °C Viscosity

Oxidising properties Not determined.

9.2. Other information

Other information None.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product. Vapours may form

explosive mixtures with air.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

Not relevant.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid exposure to high temperatures or

direct sunlight.

10.5. Incompatible materials

Materials to avoid No specific material or group of materials is likely to react with the product to produce a

hazardous situation.

10.6. Hazardous decomposition products

Hazardous decomposition

Does not decompose when used and stored as recommended.

products

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects No information available.

Carcinogenicity

Carcinogenicity Does not contain any substances known to be carcinogenic.

Reproductive toxicity

Reproductive toxicity - fertility No evidence of reproductive toxicity in animal studies.

Specific target organ toxicity - single exposure

STOT - single exposure Central nervous system depression including narcotic effects such as drowsiness, narcosis,

reduced alertness, loss of reflexes, lack of coordination and vertigo.

Target organs Central nervous system

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Morphological changes that are potentially reversible but provide clear evidence of marked

organ dysfunction.

Target organs Skin

Aspiration hazard

Aspiration hazard Not applicable. Revision date: 17/04/2019 Revision: 9 Supersedes date: 05/04/2016

A-WONDER TYRE AND TRIM

General information Prolonged and repeated contact with solvents over a long period may lead to permanent

health problems.

Inhalation Vapours may cause drowsiness and dizziness.

Ingestion No harmful effects expected from quantities likely to be ingested by accident.

Skin contact Irritating to skin.

Eye contact Vapour or spray in the eyes may cause irritation and smarting.

Acute and chronic health

hazards

This chemical can be hazardous when inhaled and/or touched. May cause severe internal

injury. Vapour from this product may be hazardous by inhalation.

Route of exposure Inhalation Skin and/or eye contact

Target organs Central nervous system Eyes Skin

Medical symptoms Skin irritation. Irritation of eyes and mucous membranes. Central nervous system depression.

Drowsiness, dizziness, disorientation, vertigo.

Medical considerations Skin disorders and allergies. Pre-existing eye problems.

SECTION 12: Ecological information

Ecotoxicity Dangerous for the environment. May cause long-term adverse effects in the aquatic

environment.

12.1. Toxicity

Acute aquatic toxicity

Acute toxicity - fish LC50, 96 hours: >13.4 mg/l (NAPHTHA (PETROLEUM) HYDROTREATED LIGHT) mg/l, Fish

Acute toxicity - aquatic

aquatic EC₅₀, 48 hours: 3 mg/l (NAPHTHA (PETROLEUM) HYDROTREATED LIGHT) mg/l, Daphnia

invertebrates magna

Acute toxicity - aquatic plants IC55, 72 hours: 10 mg/l (NAPHTHA (PETROLEUM) HYDROTREATED LIGHT) mg/l, Algae

12.2. Persistence and degradability

Persistence and degradability No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not determined.

12.4. Mobility in soil

Mobility The product is insoluble in water.

Adsorption/desorption

coefficient

Not available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB Thi

This substance is not classified as PBT or vPvB according to current EU criteria.

assessment

12.6. Other adverse effects

Other adverse effects Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste is classified as hazardous waste. Dispose of waste to licensed waste disposal site in

accordance with the requirements of the local Waste Disposal Authority. Do not puncture or

incinerate, even when empty.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority. Confirm disposal procedures with environmental engineer and

local regulations.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1950 UN No. (IMDG) 1950 UN No. (ICAO) 1950

14.2. UN proper shipping name

Proper shipping name

AEROSOLS (NAPHTHA (PETROLEUM), HYDROTREATED LIGHT)

(ADR/RID)

Proper shipping name (IMDG) AEROSOLS (NAPHTHA (PETROLEUM), HYDROTREATED LIGHT)

Proper shipping name (ICAO) AEROSOLS (NAPHTHA (PETROLEUM), HYDROTREATED LIGHT)

Proper shipping name (ADN) AEROSOLS (NAPHTHA (PETROLEUM), HYDROTREATED LIGHT)

14.3. Transport hazard class(es)

ADR/RID class 2.1

ADR/RID label 2.1

IMDG class 2.1

ICAO class/division 2.1

Transport labels



14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS F-D, S-U

Tunnel restriction code (D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations EH40/2005 Workplace exposure limits

EU legislation Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18

December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments NOTE: Lines within the margin indicate significant changes from the previous revision.

Issued by Health & Safety Department

Revision date 17/04/2019

Revision 9

Supersedes date 05/04/2016 SDS status Approved.

Hazard statements in full H220 Extremely flammable gas.

H222 Extremely flammable aerosol.
H225 Highly flammable liquid and vapour.

H229 Pressurised container: may burst if heated.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.