Revision 3

Supersedes date 06/11/2011 v2



SAFETY DATA SHEET 80W GEAR OIL

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name 80W GEAR OIL

Product No. XEP011, XEP455, XEP501, YFY025

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Engine oil.

1.3. Details of the supplier of the safety data sheet

Supplier TETROSYL LIMITED

BEVIS GREEN WORKS

WALMERSLEY

BURY BL9 6RE

0161 764 5981 0161 797 5899 info@tetrosyl.com

Manufacturer TETROSYL LIMITED

BEVIS GREEN WORKS

WALMERSLEY

BURY BL9 6RE 0161 764 5981 0161 797 5899 info@tetrosyl.com

1.4. Emergency telephone number

0161 764 5981

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical and Chemical Not classified.

Hazards

Human health Not classified. Environment Not classified.

Classification (1999/45/EEC) Not classified.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

2.2. Label elements

Label In Accordance With (EC) No. 1272/2008

No pictogram required.

Report Date: 12/03/2014 2 / 7
Revision 3

80W GEAR OIL

Precautionary Statements

P101 If medical advice is needed, have product container or label

at hand

P102 Keep out of reach of children.

2.3. Other hazards

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General information

Get medical attention if any discomfort continues. Remove affected person from source of contamination.

General first aid, rest, warmth and fresh air.

Inhalation

In case of inhalation of spray mist: Move person into fresh air and keep at rest.

Ingestion

Contact physician if larger quantity has been consumed. Rinse mouth thoroughly.

Skin contact

Promptly wash contaminated skin with soap or mild detergent and water. Promptly remove clothing if soaked through and wash as above. Contact physician if irritation continues or sores develop.

Eve contact

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Do not rub eye.

4.2. Most important symptoms and effects, both acute and delayed

General information

The severity of the symptoms described will vary dependant of the concentration and the length of exposure.

NOTE! Effects may be delayed. Keep affected person under observation.

Inhalation

May cause an asthma-like shortness of breath. Vapours may cause headache, fatigue, dizziness and nausea.

Ingestion

May cause discomfort if swallowed. May cause stomach pain or vomiting. May cause nausea, headache, dizziness and intoxication.

Skin contact

Prolonged or repeated contact with skin may cause redness, itching, irritation and eczema/chapping. Allergic rash.

Eye contact

May cause temporary eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

No recommendation given, but first aid may still be required in case of accidental exposure, inhalation or ingestion of this chemical. If in doubt, GET MEDICAL ATTENTION PROMPTLY!

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media

Use: Foam, carbon dioxide or dry powder. Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Report Date: 12/03/2014 3 / 7
Revision 3

80W GEAR OIL

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products

During fire, toxic gases (CO, CO2) are formed.

Unusual Fire & Explosion Hazards

No unusual fire or explosion hazards noted.

Specific hazards

Fire creates: Carbon monoxide (CO). Carbon dioxide (CO2).

5.3. Advice for firefighters

Protective equipment for fire-fighters Leave danger zone immediately.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Follow precautions for safe handling described in this safety data sheet. Avoid inhalation of vapours and aerosol spray. Avoid contact with eyes and prolonged skin contact. Provide adequate ventilation. In case of spills, beware of slippery floors and surfaces.

6.2. Environmental precautions

Avoid discharge into drains, water courses or onto the ground. The product should not be dumped in nature but collected and delivered according to agreement with the local authorities.

6.3. Methods and material for containment and cleaning up

Stop leak if possible without risk. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Provide ventilation and confine spill. Do not allow runoff to sewer. Collect with absorbent, non-combustible material into suitable containers.

6.4. Reference to other sections

Wear protective clothing as described in Section 8 of this safety data sheet. Collect and dispose of spillage as indicated in section 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site. Do not eat, drink or smoke when using the product. Avoid forming spray/aerosol mists. Provide good ventilation. Avoid contact with skin and eyes. Always remove oil with soap and water or skin cleaning agent, never use organic solvents. Do not use oil-contaminated clothing or shoes, and do not put rags moistened with oil into pockets.

7.2. Conditions for safe storage, including any incompatibilities

Keep upright. Store in tightly closed original container.

7.3. Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

8.2. Exposure controls

Protective equipment

Report Date: 12/03/2014 4 / 7

Revision 3

80W GEAR OIL







Engineering measures

Provide adequate ventilation. Observe Occupational Exposure Limits and minimise the risk of inhalation of vapours.

Respiratory equipment

No specific recommendations.

Hand protection

Protective gloves should be used if there is a risk of direct contact or splash. Nitrile gloves are recommended, but be aware that the liquid may penetrate the gloves. Frequent change is advisable.

Eye protection

Wear approved, tight fitting safety glasses where splashing is probable.

Other Protection

Wear suitable protective clothing as protection against splashing or contamination.

Hygiene measures

Wash contaminated clothing before reuse. Wash promptly with soap & water if skin becomes contaminated.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance Clear liquid. Colour Brown.

Odour Characteristic.
Solubility Insoluble in water

Initial boiling point and boiling >250°C

range (°C)

Melting point (°C)

Scientifically unjustified.

Relative density 0.885g/cm³ 20°C

Vapour density (air=1) Scientifically unjustified.

Vapour pressure

Scientifically unjustified.

Evaporation rate

Scientifically unjustified. pH-Value, Conc. Solution Scientifically unjustified.

Viscosity 8.5 cSt 100°C

Decomposition temperature (°C)

Scientifically unjustified.
Odour Threshold, Lower
Scientifically unjustified.
Odour Threshold, Upper
Scientifically unjustified.

Flash point (°C) 210°C

Auto Ignition Temperature (°C)

Scientifically unjustified.

Flammability Limit - Lower(%)

Scientifically unjustified.

Flammability Limit - Upper(%)

Scientifically unjustified.

Report Date: 12/03/2014 5 / 7 Revision 3

80W GEAR OIL

Partition Coefficient Scientifically unjustified.

>6

(N-Octanol/Water)

Oxidising properties Not determined.

9.2. Other information

None.

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No specific reactivity hazards associated with this product.

10.2. Chemical stability

No particular stability concerns.

10.3. Possibility of hazardous reactions

Not applicable.

10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials To Avoid

Strong oxidising substances.

10.6. Hazardous decomposition products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Toxic Dose 1 - LD 50 >5000 mg/kg (oral rat) Toxic Conc. - LC 50 >5 mg/l/4h (inh-rat)

Acute toxicity:

Petroleum Distillates (Solvents Neutral)

Health Warnings

This chemical can be hazardous when inhaled and/or touched.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

12.1. Toxicity

LC 50, 96 Hrs, Fish mg/l >100 mg/l Petroleum Distillates (Solvents Neutral) EC 50, 48 Hrs, Daphnia, mg/l >100 mg/l Petroleum Distillates (Solvents Neutral) IC 50, 72 Hrs, Algae, mg/l

Petroleum Distillates (Solvents Neutral)

Report Date: 12/03/2014 6 / 7
Revision 3

80W GEAR OIL

12.2. Persistence and degradability

Degradability

No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential

No data available on bioaccumulation.

Partition coefficient

Scientifically unjustified. >6

12.4. Mobility in soil

Mobility:

The product is insoluble in water.

Adsorption/Desorption Coefficient

Not available.

12.5. Results of PBT and vPvB assessment

Not Classified as PBT/vPvB by current EU criteria.

12.6. Other adverse effects

Not available.

SECTION 13: DISPOSAL CONSIDERATIONS

General information

Waste is classified as hazardous waste. Disposal to licensed waste disposal site in accordance with the local Waste Disposal Authority.

13.1. Waste treatment methods

Confirm disposal procedures with environmental engineer and local regulations.

SECTION 14: TRANSPORT INFORMATION

14.1. UN number

14.2. UN proper shipping name

14.3. Transport hazard class(es)

14.4. Packing group

14.5. Environmental hazards

14.6. Special precautions for user

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Report Date: 12/03/2014 7 / 7
Revision 3

80W GEAR OIL

EU Legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.

15.2. Chemical Safety Assessment

No chemical safety assessment has been carried out.

SECTION 16: OTHER INFORMATION

Revision Comments

NOTE: Lines within the margin indicate significant changes from the previous revision.

Revision Date 12/03/2014

Revision 3

Supersedes date 06/11/2011 v2 Safety Data Sheet Status Approved.

Risk Phrases In Full

NC Not classified.

Hazard Statements In Full